

HAZARD RATING
4=EXTREME
3=HIGH
2=MODERATE
1=SLIGHT
0=INSIGNIFICANT

HEALTH	1
FLAMMABILITY	3
REACTIVITY	0

SAFETY DATA SHEET
CLEAR ULTRA SHEEN 7000

SECTION I - GENERAL INFORMATION

PRODUCT IDENTIFICATION: CLEAR ULTRA SHEEN 7000	
VOC CONTENT:	<350 GRAMS/LITER OR <2.92 #/GAL
CATEGORY:	CONCRETE CURING COMPOUND
COMMON NAME:	STYRENE ACRYLATE COPOLYMER IN AROMATIC/EXEMPT SOLVENT
SUPPLIER	STAMPCRETE INTERNATIONAL
ADDRESS	325 COMMERCE BLVD. LIVERPOOL, NY 13088
TELEPHONE NO.	800-233-3298
MANUFACTURER:	VEXCON CHEMICALS, INC
ADDRESS	7240 STATE RD, PHILADELPHIA, PA 19135
EMERGENCY NO:	800.858.2828 (PolySat Inc)
TELEPHONE NO:	215.332.7709 (Vexcon)
CHEMTREC NO:	800.424.9300 (CCN# 23822)
PREPARED:	AUGUST 2003
UPDATED:	MAY 2014
PREPARED BY:	DARRY F. MANUEL , PRESIDENT

SECTION II - HAZARD IDENTIFICATION

DOT SHIPPING NAME:

UN ID NUMBER / SHIPPING NAME / HAZARD CLASS / PKG GROUP
IN CONTAINERS LESS THAN 119 GALS:

**UN 1866, RESIN SOLUTION, FLAMMABLE, 3, PGII, RQ
(TERTIARY BUTYL ACETATE)**

IN CONTAINERS GREATER THAN 119 GALS:
**UN 1866, RESIN SOLUTION, FLAMMABLE, 3, II, RQ
(TERTIARY BUTYL ACETATE)**



FOR LIMITED QUANTITY AIR & OCEAN SHIPMENT:

UN 1866, RESIN SOLUTION (TERTIARY BUTYL ACETATE), FLAMMABLE, 3, II, LIMITED QUANTITY

LTD QTY Limits:

Passenger Air Limit 60L (15.8gal);
Cargo Air Limit 220L (58.1gal)

ORM-D: MAX. 30 Kg gross wt

HEALTH AND SAFETY: FLAMMABLE OR COMBUSTIBLE LIQUID: USE ONLY WITH ADEQUATE VENTILATION: IF SWALLOWED, DO NOT INDUCE VOMITING: USE OF SOLVENT RESISTANT GLOVES, GOGGLES AND OTHER PROTECTIVE EQUIPMENT IS ADVISED WHEN HANDLING THIS PRODUCT: ASPIRATION OF MATERIAL INTO THE LUNGS CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL: USE OF RESPIRATORS IS ADVISED WHEN USING PRODUCT IN CONFINED AREA.



SECTION III HAZARDOUS INGREDIENTS

MATERIAL OR COMPONENTS	CAS NO.	%	HAZARD DATA	UN#
STYRENE ACRYLATE POLYMER	25036-16-2	35-45%	ND	NONE
TERTIARY BUTYL ACETATE	540-88-5	35-45%	OSHA HAZARD: FLAMMABLE LIQUID OSHA PEL: 200 ppm ACGIH TLV: 200 ppm	1123
HEAVY AROMATIC SOLVENT NAPHTHA	64742-94-5	1-5%	ACGIH TLV: 100 ppm, 525 mg/m3 (TWA) OSHA PEL: 500 ppm, 2900 mg/m3 (TWA) NIOSH REL: 350 mg/m3 (TWA)	1255
SOLVENT NAPHTHA (Petroleum) LIGHT AROMATIC	64742-94-6	<5%	OSHA HAZARD: COMBUSTIBLE TLV 50 ppm	1268
THE SOLVENT PORTION CONTAINS THE FOLLOWING SECTION 313 REPORTABLE INGREDIENTS:				
1,2,4 TRIMETHYL BENZENE	95-63-6	1.5% Max	DOT LABEL: FLAMMABLE OSHA PEL not regulated ACGIH TLV 25 ppm (TWA) NIOSH REL: 25 ppm (TWA)	1993
CUMENE	98-82-8	1.1% Max	OSHA PEL: 50 ppm (TWA) ACGIH TLV 50 ppm (TWA)	1918
XYLENE	1330-20-7	2.2% Max	DOT LABEL: FLAMMABLE LIQUID OSHA PEL: 100 ppm (TWA) ACGIH TLV 100 ppm (TWA)	1307

SECTION IV FIRST AID MEASURES

**HEALTH HAZARD DATA HAZARD CLASSIFICATION
BASIS FOR CLASSIFICATION SOURCE**

ROUTES OF EXPOSURE:	
INHALATION:	THIS PRODUCT MAY CREATE BREATHING DIFFICULTIES. DIZZINESS, LIGHTHEADEDNESS WHEN WORKING IN AREAS WITH HIGH VAPOR CONCENTRATION. AROMATIC 100 ,AROMATIC150, AND TERT BUTYL ACETATE COMPONENTS.
SKIN CONTACT:	THIS PRODUCT MAY CAUSE SKIN IRRITATION UPON PROLONGED OR REPEATED CONTACT. AROMATIC 100 ,AROMATIC150, AND TERT BUTYL ACETATE COMPONENTS.
SKIN ABSORPTION:	THIS PRODUCT MAY CAUSE SKIN IRRITATION UPON PROLONGED OR REPEATED CONTACT. AROMATIC 100 ,AROMATIC150, AND TERT BUTYL ACETATE COMPONENTS.
EYE CONTACT:	THIS PRODUCT MAY BE AN EYE IRRITANT. AROMATIC 100 ,AROMATIC150, AND TERT BUTYL ACETATE COMPONENTS.
INGESTION / INHALATION	SMALL AMOUNTS OF LIQUID ASPIRATED INTO THE RESPIRATORY SYSTEM DURING INGESTION, OR FROM VOMITING, MAY CAUSE BRONCHOPNEUMONIA OR PULMONARY EDEMA. DO NOT INDUCE VOMITING. SEEK IMMEDIATE MEDICAL ATTENTION.
EFFECTS OF OVEREXPOSURE:	TLV 50 ppm ANESTHESIA, HEADACHE, NAUSEA, DIZZINESS. LIQUIDS MODERATELY IRRITATING ON SKIN AND EYES.

ACUTE OVEREXPOSURE:	ANESTHESIA, HEADACHE, NAUSEA, DIZZINESS: MODERATE IRRITATION BY LIQUID TO SKIN AND EYES. PROLONGED CONTACT ON THE SKIN WILL CLAY AND DEBAT THE SKIN POSSIBLY CAUSING DERMATITIS.
EMERGENCY AND FIRST AID PROCEDURES:	
EYES:	FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. SEEK IMMEDIATE MEDICAL ATTENTION.
SKIN:	WASH WITH SOAP AND LARGE QUANTITIES OF WATER. SEEK MEDICAL ATTENTION IF SKIN IRRITATION DEVELOPS AND PERSISTS.
INHALATION:	MOVE TO LOCATION FREE FROM VAPORS. IF BREATHING STOPS, BEGIN ARTIFICIAL RESPIRATION AND SEEK IMMEDIATE MEDICAL ATTENTION.
INGESTION:	DO NOT INDUCE VOMITING; SEEK IMMEDIATE MEDICAL ATTENTION.

SECTION V FIREFIGHTING MEASURES

EXTINGUISHING MEDIA:	FIRES INVOLVING THIS PRODUCT MAY BE CONTROLLED BY CARBON DIOXIDE, DRY CHEMICALS OR WATER SPRAY. WATER MAY BE USED TO REDUCE THE RATE OF BURNING AND FOR COOLING PURPOSES. AVOID SPRAYING WATER DIRECTLY INTO STORAGE CONTAINERS DUE TO DANGER OF BOIL OVER. THE USE OF SELF-CONTAINED BREATHING APPARATUS IS RECOMMENDED FOR FIRE FIGHTERS.SEE ALSO SECTION IX.
GENERAL HAZARD:	FLAMMABLE LIQUID - CAN FORM COMBUSTIBLE MIXTURES AT TEMPERATURES AT OR ABOVE THE FLASH POINT. STATIC DISCHARGE - MATERIAL CAN ACCUMULATE STATIC CHARGES WHICH CAN CAUSE AN INCENDIARY ELECTRICAL DISCHARGE. "EMPTY" CONTAINERS RETAIN PRODUCT RESIDUE (LIQUID AND/OR VAPOR) AND CAN BE DANGEROUS. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. EMPTY DRUMS SHOULD BE COMPLETELY DRAINED, PROPERLY BUNGED AND PROMPTLY RETURNED TO A DRUM RECONDITIONER, OR PROPERLY DISPOSED OF.
ELECTRO-STATIC ACCUMULATION HAZARD:	USE PROPER GROUNDING
UNUSUAL FIRE AND EXPLOSION HAZARD:	THIS PRODUCT IS EXTREMELY FLAMMABLE AND EXPLOSIVE UNDER NORMAL CONDITIONS IN THE PRESENCE OF FLAME OR SPARK SOURCE. IF STORAGE CONTAINERS ARE EXPOSED TO EXCESSIVE HEAT, OVER PRESSURIZATION OF THE CONTAINERS CAN RESULT.VAPOR IS HEAVIER THAN AIR AND MAY TRAVEL ALONG THE GROUND OR THROUGH VENTILATION SYSTEM CONSIDERABLE DISTANCE TO A SOURCE OF IGNITION AND FLASH BACK. KEEP WORK AREAS FREE OF HOT METAL SURFACES AND OTHER SOURCES OF IGNITION.
SPECIAL FIRE FIGHTING PROCEDURES	THE USE OF SELF-CONTAINED BREATHING APPARATUS WITH FULL FACE PIECE OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE SHOULD BE PROVIDED FOR FIRE FIGHTERS IN BUILDINGS OR CONFINED AREAS WHERE THIS PRODUCT IS STORED. STORAGE CONTAINERS EXPOSED TO FIRE SHOULD BE KEPT COOL WITH WATER SPRAY IN ORDER TO PREVENT PRESSURE BUILD UP. KEEP WORK AREAS FREE OF HOT METAL SURFACES AND OTHER SOURCES OF IGNITION.

SECTION VI ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:
LAND SPILL: ELIMINATE SOURCES OF IGNITION. PREVENT ADDITIONAL DISCHARGE OF MATERIAL; IF POSSIBLE TO DO SO WITHOUT HAZARD. FOR SMALL SPILLS, IMPLEMENT CLEANUP PROCEDURES. FOR LARGE SPILL, IMPLEMENT CLEAN UP PROCEDURES AND, IF IN PUBLIC AREA, KEEP PUBLIC AWAY AND ADVISE AUTHORITIES. ALSO, IF THIS PRODUCT IS SUBJECT TO CERCLA REPORTING NOTIFY THE NATIONAL RESPONSE CENTER. PREVENT LIQUID FROM ENTERING SEWERS, WATERCOURSES, OR LOW AREAS. CONTAIN SPILLED LIQUID WITH SAND OR EARTH. DO NOT USE COMBUSTIBLE MATERIALS SUCH AS SAWDUST. RECOVER BY PUMPING (USE AN EXPLOSION PROOF OR HAND PUMP) OR WITH A SUITABLE ABSORBENT. CONSULT AN EXPERT ON DISPOSAL OF RECOVERED MATERIAL AND ENSURE CONFORMITY TO EPA, FEDERAL, STATE, AND LOCAL DISPOSAL REGULATIONS. WATER SPILL: REMOVE FROM SURFACE BY SKIMMING OR WITH SUITABLE ABSORBENTS. IF ALLOWED BY LOCAL AUTHORITIES AND ENVIRONMENTAL AGENCIES, SINKING AND/OR SUITABLE DISPERSANTS MAY BE USED IN NON-CONFINED WATERS. CONSULT AN EXPERT ON DISPOSAL OF RECOVERED MATERIAL AND ENSURE CONFORMITY TO EPA, FEDERAL, STATE, AND LOCAL DISPOSAL REGULATIONS.

SECTION VII HANDLING AND STORAGE

PRECAUTIONARY STATEMENTS: PERSONNEL SHOULD AVOID INHALATION OF VAPORS. PERSONAL CONTACT WITH THE PRODUCT SHOULD BE AVOIDED. SHOULD CONTACT BE MADE, REMOVE SATURATED APPAREL AND FLUSH AFFECTED BODY AREAS WITH WATER. CLOTHING MUST BE WASHED AND DRIED BEFORE REUSE. CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUE (VAPOR, LIQUID AND/OR SOLID). ALL HAZARD PRECAUTIONS GIVEN IN THIS DATA SHEET MUST BE OBSERVED.
FIRE FIGHTING: WATER MAY BE UNSUITABLE AS AN EXTINGUISHING MEDIUM BUT HELPFUL IN KEEPING ADJACENT CONTAINERS COOL. AVOID SPREADING BURNING LIQUID WITH WATER USED FOR COOLING PURPOSES. PERSONNEL SHOULD AVOID INHALATION OF VAPORS.
OTHER HANDLING AND STORAGE REQUIREMENTS: STORE AND USE IN WELL VENTILATED AREA, EQUIVALENT TO FRESH AIR. KEEP CONTAINER TIGHTLY CLOSED. DO NOT STORE WITH INCOMPATIBLE MATERIALS. STORE IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS. DO NOT STORE OR CONSUME FOOD, DRINK, OR TOBACCO IN AREAS WHERE THEY MAY BECOME CONTAMINATED WITH THIS MATERIAL. KEEP AWAY FROM HIGH TEMPERATURES, OPEN FLAMES, SPARKS, SOURCES OF IGNITION, ETC. USE WITH EXPLOSION PROOF EQUIPMENT IS HIGHLY ADVISABLE.

SECTION VIII EXPOSURE CONTROLS / PERSONAL PROTECTION

VENTILATION REQUIREMENTS: LOCAL MECHANICAL VENTILATION MAY BE SUFFICIENT TO KEEP PRODUCT VAPOR CONCENTRATIONS WITHIN SPECIFIED TIME-WEIGHTED TLV RANGES. IF LOCAL VENTILATION PROVES INADEQUATE TO MAINTAIN SAFE VAPOR CONCENTRATIONS, SUPPLEMENTAL LOCAL EXHAUST MAY BE REQUIRED. OTHER SPECIAL PRECAUTIONS SUCH AS RESPIRATORY MASKS OR ENVIRONMENTAL CONTAINMENT DEVICES MAY BE REQUIRED IN EXTREME CASES.
RESPIRATORY (SPECIFY IN DETAIL): THE USE OF RESPIRATORY PROTECTION DEPENDS ON VAPOR CONCENTRATION ABOVE THE TIME WEIGHTED TLV: USE OF OSHA APPROVED CARTRIDGE RESPIRATOR OR GAS MASK OR AIR-PACK. CHEMICAL CARTRIDGE RESPIRATOR: HALF MASK ORGANIC VAPOR CARTRIDGE. FULL FACE ORGANIC VAPOR CARTRIDGE IF EYE PROTECTION IS NEEDED.
EYES: CHEMICAL GOGGLES AND/OR FACE SHIELD ARE RECOMMENDED TO SAFEGUARD AGAINST POTENTIAL EYE CONTACT, IRRITATION OR INJURY.
GLOVES: THE USE OF IMPERMEABLE GLOVES IS ADVISED TO PREVENT SKIN IRRITATION IN SENSITIVE INDIVIDUALS. IMPERVIOUS GLOVES, (CHEMICAL RESISTANT) SUCH AS NEOPRENE, LATEX OR PVA.
OTHER CLOTHING AND EQUIPMENT: TO PREVENT BODY CONTACT, IMPERVIOUS CLOTHING AND BOOTS ARE RECOMMENDED. IMPERVIOUS APRONS AND HELMETS (HEAD COVER) ARE RECOMMENDED WHEN WORKING WITH THIS PRODUCT. THE AVAILABILITY OF EYE WASHES AND SAFETY SHOWERS IN WORK AREAS IS RECOMMENDED.

SECTION IX PHYSICAL / CHEMICAL CHARACTERISTICS

BOILING POINT: (760mmHg) 98 C / 208 F (TERT BUTYL ACETATE)	MELTING POINT: -62 C, -79 F (tert butyl acetate)
VAPOR PRESSURE: 41 mmHg@77°F/25°C (tert butyl acetate)	VAPOR DENSITY (AIR=1): 2.0 (tert butyl acetate)
SOLUBILITY IN H2O % BY WT: 0.5%	% VOLATILES BY VOL: 65-70%
EVAPORATION RATE (BuAc=1): MEDIUM 2.8 (tert butyl acetate)	SPECIFIC GRAVITY (H2O=1) 0.930
pH (AS IS) N/A	pH (1% SOLN) N/A
APPEARANCE AND ODOR:	CLEAR LIQUID WITH SWEET SOLVENT ODOR
FLASH POINT: (TEST METHOD)	4.4°C / 40°F (TCC) [tert butyl acetate]
AUTOIGNITION TEMP:	518°C / 964°F (tert butyl acetate)
FLAMMABLE LIMITS IN AIR, % BY VOL:	LOWER: 1.26% UPPER: 6.88% (tert butyl acetate)

SECTION X STABILITY AND REACTIVITY

CONDITIONS CONTRIBUTING TO INSTABILITY:	THIS PRODUCT IS STABLE.
INCOMPATIBILITY:	THIS PRODUCT IS INCOMPATIBLE WITH STRONG OXIDIZING AGENTS, STRONG ACIDS OR BASES, AND SELECTED AMINES.
HAZARDOUS DECOMPOSITION PRODUCTS:	THERMAL DECOMPOSITION IN THE PRESENCE OF AIR MAY YIELD CARBON MONOXIDE AND/OR CARBON DIOXIDE, AND UNIDENTIFIED ORGANICS.
CONDITIONS CONTRIBUTING TO HAZARDOUS POLYMERIZATION:	N/A WILL NOT OCCUR

SECTION XI TOXICOLOGICAL INFORMATION

ACUTE TOXICITY	LC50 (VAPOR)	RAT	4211 ppm	6 HOURS
	LD50 (ORAL)	RAT	4500 MG/KG BWT	
	LD50	RABBIT	>2000 ,G/KG BWT	
ACUTE EFFECTS	INHALATION		VAPORS OR AEROSOL MAY CAUSE IRRITATION OF THE EYES, NOSE AND THROAT AS WELL AS CNS DEPRESSION (FATIGUE, DIZZINES, LOSS OF CONCENTRATION, WITH COLLAPSE, COMA AND DEATH POSSIBLE IN CASES OF SEVERE OVER EXPOSURE), INHALATION OF AIRBORNE DROPLETS MAY CAUSE IRRITATIONS OF THE RESPIRATORY TRACT.	
	INGESTION		MAY CAUSE CNS DEPRSSION, GASTRIC DSCOMFORT, AND VOMITING. THIS MATERIAL IS AN ASPIRATION HAZARD.	
	SKIN CONTACT		NO SYSTEMIC TOXICITY IS EXPECTED FROM ACUTE DERMAL EXPOSURE	
IRRITATION	SKIN		NOT A SKIN IRRITANT	
	EYES		NO EYE IRRITATION	
SENSITIZATION	DOES NOT INDUCE SKIN SENSITIZATION.			
REPEATED DOES TOXICITY	INHALATION REPEATED EXPOSURE STUDIES DEMONSTRATED TARGET ORGAN EFFECTS IN MALE RATS (KINDEY) BY MECHANISM OF ACTION THAT IS NOT RELEVANT TO HUMAS NAD IN MICE (NERVOUS SYTEM) TRANSIENT BEHAVIOR CHANGES THAT WERE OBSERVED IMMEDIATELY AFTER EXPOSURE.			
REPRODUCTIVE EFFEXTE	THIS SUBSTANCE IS NOT TOXIT TO REPRODUCTION. THE REPRODUCTIVE TOXICITY OF T-BUTYL ACETATE HAS BEEN INVESTAGATED IN RATS VIA A INHALATION ROUTE. THERE WERE NO ADVERSE EFFECTS ON REPRODUCTIVE PERFORMANCE OR SPERM NUMVER OR UALITY AT 1600 ppm, THE HIGHEST EXPOSURE LEVEL TESTED. IN ADDITION, NO GROSS OR HISTOPATHOLOGIC EFFECTS WERE OBSERVED IN THE REPRODUCTIVE ORGANS OF MALE AND FEMALE RATS OR MICE EXPOSED AT 1600 ppm FOR 90 DAYS IN A REPEATED EXPOSURE TOXICITY STUDY CONDUCTED VIA INHALATION AND THERE WAS NO ADVERSE EFFECTS ON ESTROUS CYCLE LENGTH IN MICE.			
DEVELOPMENTAL TOXICITY	THIS SUBSTANCE IS NOT A DEVELOPMENTAL TOXICANT. IT DID NOT CAUSE MATERNAL TOXICITY AND NO EMBRO/FETAL TOXICITY OR DEVELOPMENTA ABNORMALITIES WERE OBSERVED IN THE OFF SPRINF OF ANIMALS FOLLOWING INHALATION EXPOSURES OF 1600			

	ppm.
GENETIS TOXICITY	NEGATIVE FOR GENOTOXICITY USING BOTH IN VITRO AND IN VIVO TEST.
GARCINOGENICITY	SPECIFIC DATA NOT AVAILABLE. T-BUTANOL, THE PRIMARY METABOLITE OF T-BUTYL ACETATE IS AN ANAMAL CARCINOGEN. IN DRINKING WATER STUDY, T-BUTANOL INDUCED BEGIGN KIDNEY TUMORS IN MALE RATS VIA AN a-2u-GLOBULIN MODE OF ACTION, A TUMOR MECHANISM NOT RELEVANT TO HUMANS. IN FEMAL MICE, THERE WAS AN INCREASE INCIDENCE OF BEGIGN THYROID TUMORS, A TUMOR MECHANISM THAT MOST LIKELY IS NOT RELEVANT TO HUMAND. THIS SUBSTANCE IS NOT CLASSIIIFIED FOR CARCINOGENICITY BY IARC, OSHA, NTP OR THE EPA.

SECTION XII ECOLOGICAL INFORMATION

ECOTOXICITY	ACUTE FISH TOXICITY	LC50/96 HOURS	ONCORHYN CHUS MYKISS 240 mg/l	ACUTE TOXICITY TO FISH IS LOW
	ACUTE TOXICITY TO AQUATIC INVERTEBRATES	EC50/48 HOURS	DAPHNIA MAGNE 350 mg/l	LOW ACUTE TOXICITY TO AQUATIC INVERTEBRAT ES.
	TOXICITY TO AQUATIC PLANTS	EC/5096 HOURS	PSEUDOKIR CHNERIELL A SUBCAPITA TA 60 mg/l	LOW TOXICITY TO ALGAE
	TOXICITY TO MICROORGANISMS	EC3/16 HOURS	PSEUDOMO NAS PUTIDA 78 mg/l	LOW TOXICITY TO BACTERIA
		EC3/72 HOURS	ENTOSPIHO N SULCATUM 970 mg/l	
	CHRONIC TOXICITY TO FISH	NO DATA AVAILABLE		
	CHRONIC TOXICITY TO AQUATIC INVERTEBRATES	NON DATA AVAILABLE		
OTHER ADVERSE EFFECTS	EXPECTED TO SHOW LOW TOXICITY TO HIGHER PLANTS			
ENVIRONMENTAL FATE AND PATHWAYS	EXPECTED TO BE EMMITTED AND PARTITION PREDOMINANTLY TO THE ATMOSPHERE. ACCIDENTAL RELEASES TO WATER OR SOIL ARE EXPECTED TO EVAPORATED AND UNDERGO ATMOSPHERIC DECOMPOSITION PROCESSES.			
	MOBILITY	BEHAVIOR IN ENVIRONMENTAL COMPARTMENTS; RELEASED MATERIAL WOULD BE EXPECTED TO SHOW HIGH SOIL MOBILITY AND TO VOLATILIZE READILY FORM SOIL NAD SURFACE WATERS, FORMING ATMOSPHERIC VAPOR.		
	PERSISTENCE AND DEGRADABILITY	BIODEGRADATION: EXPECTED TO HYDROLYZE SLOWLY IN WATER (HALF-LIFE CA 0.5 YEARS OR LONGER). ATMOSPHERIC VAPORS EXPECTED TO BE PHOTOCHEMICALLY DEGRADED BY REACTION WITH HYDROXYL RADICALS (HALS LIKE 19.7 DAYS). INHERENTLY BIODEGRADABLE.		
	OTHE ADVERSE EFFECTS	BIOACCUMULATION: BIOCONCENTRATION FACTOR (BCF) 5.61 (QSAR CALCULATED VALUE)) THIS MATERIAL IS NOT EXPECTED TO BIOACCUMULATE. THIS MATERIAL IS NOT CONSIDERED PERSISTENT BY EPA, AND IS NOT EXPECED TO CONTRIBUTE TO THE GREENHOUSE GAS EFFECT, STRATOSPHERIC OZONE DEPLETION. TROPOSPHERIC OZONE FORMATION, OR PARTICULATE MATTER FORMATION.		

SECTION XIII DISPOSAL CONSIDERATIONS

AQUATIC TOXICITY (E.G. 96 HR. TLM): DO NOT DISCHARGE THIS PRODUCT INTO PUBLIC WATERS OR WATERWAYS UNLESS AUTHORIZED BY A NATIONAL POLLUTION DISCHARGE ELIMINATION SYSTEM (NPDES) PERMIT ISSUED BY THE ENVIRONMENTAL PROTECTION AGENCY (EPA).
WASTE DISPOSAL METHOD: IF POSSIBLE, PUMP TO CONTROLLED CONTAINMENT AREA. ABSORB ON CLAY OR SAND. DISPOSE OF IN COMPLIANCE WITH EPA, FEDERAL, STATE, AND LOCAL REGULATIONS. TREATMENT TRANSPORTATION AND DISPOSAL MUST BE IN COMPLIANCE WITH EPA FEDERAL, STATE, AND LOCAL REGULATIONS UNDER THE RESOURCES CONSERVATION AND RECOVERY ACT (RCRA, 40 CFR 261). TYPICALLY CONTROLLED BURNING, INCINERATION OR APPROVED LAND FILL SITES ARE AVAILABLE.

SECTION XIV TRANSPORTATION INFORMATION

Governing Body	Mode	UN Number	Proper Shipping Name	Hazard Class	Packing Group
DOT	GROUND	1866	RESIN SOLUTION (TERTIARY BUTYL ACETATE)	FLAMMABLE , 3	II
IATA	AIR	1866	RESIN SOLUTION (TERTIARY BUTYL ACETATE)	FLAMMABLE , 3	II
IMDG	OCEAN	1866	RESIN SOLUTION (TERTIARY BUTYL ACETATE)	FLAMMABLE , 3	II
MARINE POLLUTANT:	THIS PRODUCT DOES CONTAIN A MATERIAL ON THE MARINE POLLUTANTS TABLE (HMT 172.101 APPENDIX B) TERTIARY BUTYL ACETATE)				

SECTION XV REGULATORY INFORMATION

TSCA: THE SOLVENT PORTION OF THIS PRODUCT IS LISTED ON THE TSCA INVENTORY AS A UVCB (UNKNOWN, VARIABLE COMPOSITION OR BIOLOGICAL) CHEMICAL AT CAS REGISTRY NUMBER 64742-95-6 (aromatic 100). 540-88-5 (tertiary butyl acetate).
CERCLA: IF THE REPORTABLE QUANTITY OF THIS PRODUCT IS ACCIDENTALLY SPILLED, THE INCIDENT IS SUBJECT TO THE PROVISIONS OF THE COMPREHENSIVE ENVIRONMENTAL RESPONSE COMPENSATION AND LIABILITY ACT (CERCLA) AND MUST BE REPORTED TO THE NATIONAL RESPONSE CENTER BY CALLING 1-800-424-8802 or 202-426-2675. THE REPORTABLE SPILL QUANTITY (RQ) OF THIS PRODUCT IS 5,000 POUNDS (BUTYL ACETATE).
SARA TITLE III: UNDER THE PROVISIONS OF TITLE III, SECTIONS 311/312 OF THE SUPERFUND AMENDMENTS AND RE-AUTHORIZATION ACT, THIS PRODUCT IS CLASSIFIED INTO THE FOLLOWING HAZARD CATEGORIES: DELAYED HEALTH, FIRE
ADDITIONAL REGULATORY CONCERNS: (FEDERAL, FDA, USDA, CPSC, STATE, OTHER)
FEDERAL / FDA / USDA:
MARINE POLLUTANTS: THIS PRODUCT DOES CONTAIN A MATERIAL ON THE MARINE POLLUTANTS TABLE (HMT 172.101 Appendix B). SEE SECTION XIV
CERCLA / RQ: 5000 POUNDS (ACETONE, BUTYL ACETATE) THIS PRODUCT CONTAINS A MATERIAL ON THE RQ TABLE (HMT 172.101 Appendix A): BUTYL ACETATE
TSCA: IS THIS PRODUCT, OR ALL ITS INGREDIENTS, BEING CERTIFIED FOR INCLUSION ON THE TOXIC SUBSTANCES CONTROL ACT INVENTORY OF CHEMICAL SUBSTANCES? YES

SECTION XVI OTHER INFORMATION

PREPARED BY	DARRYL MANUEL / PRESIDENT
COMPANY:	VEXCON CHEMICALS, INC.
ADDRESS:	7240 STATE RD., PHILA., PA 19135 USA
THE INFORMATION PROVIDED IN THIS MATERIAL SAFETY DATA SHEET HAS BEEN OBTAINED FROM SOURCES BELIEVED TO BE RELIABLE. VEXCON PROVIDES NO WARRANTIES, EXPRESSED OR IMPLIED, AND ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN.	

HMIS HAZARD RATINGS:

THIS INFORMATION IS FOR PEOPLE TRAINED IN: NATIONAL PAINT AND COATINGS ASSOCIATIONS (NPCA) HAZARDOUS MATERIALS IDENTIFICATION SYSTEM (HMIS) NATIONAL FIRE PROTECTION ASSOCIATION (NFPA 704) IDENTIFICATION OF FIRE HAZARDS OF MATERIALS			KEY 4 -- SEVERE
CLEAR ULTRA SHEEN 7000	NPCA-HMIS	NFPA 704	3 -- SERIOUS
HEALTH	1	1	2 -- MODERATE
FLAMMABILITY	3	3	1 -- SLIGHT
REACTIVITY	0	0	0 -- MINIMAL